



## **Technical facts**

Size: Knuckle diameter: Hinge pin diameter: Hinge pin: Spring core:

Recommended fixation:

Packing unit:





120,0 mm

Stainless steel

10 hinges

Sleeve: brass, Spring: spring steel Stainless steel spring (additional charge)

Door leaf (directly): counter-sunk screw M5 x 10 with hexagon socket (6 pieces included)

17 mm

12 mm



## **Tender specification**

SYSKO-Stainless steel butt hinge Type: SYS-ES13-2/3 for rebated partition walls suitably for 13 mm high pressure laminate panels 3-parts butt hinge for fixation to door leaf without cutout Hinge surface ground stainless steel Available as standard hinge (ES13-2/3S) or spring hinge (ES13-2/3F)

Article	Description	Order number
ES13-2/3S DIN L	Standard hinge ground stainless steel	84ES1323SL
ES13-2/3S DIN R	Standard hinge ground stainless steel	84ES1323SR
ES13-2/3F DIN L	Spring hinge ground stainless steel	84ES1323FL
ES13-2/3F DIN R	Spring hinge ground stainless steel	84ES1323FR
Additional charge	Sleeve: brass, Spring: stainless steel	MP84FKFES120



Notes

Last-update 05/2012 Hinges 3.22